

ZXT15D2

**Dual Voice Coil
Subwoofer 38 cm**

Power Handling
3500 Watts RMS / 7000 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	100 mm
Voice Coil Winding Height		57,5 mm
Max. Linear Excursion	Xmax	+/- 23 mm
Max. Mechanical Excursion	Xmax (Peak)	+/- 30 mm
Cone Area	Sd	780 cm ²
Moving Mass	Mms	391 g
DC Resistance	Re	2 x 2 Ohms
Resonance Frequency	Fs	35 Hz
Mechanical Q-Factor	Qms	3,57
Electrical Q-Factor	Qes	0,73
Total Q-Factor	Qts	0,61
Equivalent Air Volume	VAS	45 L
VC Inductance	Le	2,15 mH
Flux Density	B/L	21,7 N/A
Efficiency 1W/1m	SPL	85 dB

Recommended Enclosure

Ported Box	
Vented Volume:	85 L
Port Diameter:	2x 100 mm
Port Area:	160 cm ²
Port Length:	28 cm
Tuning Freq. (Fb):	37 Hz
-3 dB Rolloff (F3):	29 Hz

Mechanical Components

- Diecast Aluminium Basket
- Carbon Composite Cone
- Foam Surround
- Carbon Dustcap
- Triple Nomex Spider
- Triple Magnet 3 x 100 oz (8.505 g)
- Magnet Size: Ø220 x 60 mm
- BASV Voice Coil Former

Dimensions & Weight

External Diameter:	392 mm
Mounting Diameter:	358 mm
Mounting Depth:	251 mm
Shipping Weight:	24,2 kg

